

FRISKVAND



HOSHIZAKI

DIM-30DE-1 ICE DISPENSER



Product Description

The DIM-30DE-1 produces cubed ice and has a new exterior design. The freshly produced ice does not come in contact with light or air when stored and therefore maintains the highest quality. Its ice is very well suited for multiple environments including food and beverage, leisure and healthcare.

- Portion control can be easily set, making it easy to regulate the consumption of ice among end-users, reducing energy consumption and waste.
- Hoshizaki ice dispensers are more compact with reduced space requirements and in line with modern interiors.
- Due to the auger system the water consumption is equal to the ice production.



Ice Type: Cube
Size: 28 x 28 x 32 mm

Production

Model	Ice Production per 24h (Approx.)	Temperature	Ice Production per Cycle (Approx.)	Water Consumption per 24h (Approx.)	Storage Capacity (Approx.)	Ice Dispensing Rate
DIM-30DE-1	32 / 34kg 33 / 35kg 27 / 31kg	AT.10°C, WT.10°C AT.21°C, WT.15°C AT.32°C, WT.21°C	0.6kg / 27pcs	0.20m ³ 0.21m ³ 0.175m ³	15kg	1700g / min

Specifications

Specification	DIM-30DE-1
Dimensions W x D x H (mm)	350 x 526 x 1590 (-1635)
AC Supply Voltage	1 Phase 220 - 240 / 230V, 50 / 60Hz
Electric Consumption	Rated Motor 320 / 330W
Insulation	Polyurethane Foam
Ice Dispensing System	Screw Rotated By Push Switch
Heat Rejection	600 / 630W
Refrigerant Charge	R134a

Operation Requirements
Ambient Temperature: 1 - 40°C
Water Supply Temperature: 5 - 35°C
Water Supply Pressure: 0.05 - 0.78MPa (0.5 - 8 bar)
Voltage Range: 198 - 254V +/- 6 / 10%
Accessories
Mounting Brace (Wall mounting), Installation Kit

FRISKVAND



DIM-30DE-1 ICE DISPENSER

