



# THE WORLD'S QUIETEST COMMERCIAL BLENDER

Winner of the National Restaurant Association's prestigious 2013 Kitchen Innovations Award, the Stealth 875 combines durability, power, and a wealth of exciting features. Simply put, it's the quietest, most advanced commercial blender on the market.

## **STEALTH** 875 ™

**COLOR OPTIONS** 





**BLACK** 

**IN-COUNTER** 

#### STEALTH TECHNOLOGY™ ENSURES AN UNINTERRUPTED ATMOSPHERE

The Stealth 875 includes a sleek sound enclosure and proprietary airflow innovations that enable operation at nearly the sound level of a normal conversation.

### CUSTOMIZABLE CYCLES PROVIDE CONSISTENT RESULTS EVERY TIME

In addition to 42 preprogrammed cycles, users can create custom blends with the online Blend Wizard $^{\text{TM}}$ , then store up to 14 on the blender for one-touch operation.

#### **BUILT TO SAVE TIME AND MONEY**

All Blendtec blenders are built to meet the unique needs of the commercial customer. Each feature—from top to bottom—delivers effortless operation and is designed to reduce overall cost.



BPA-FREE FOURSIDE JAR

4 SIDES
FOR A BETTER BLENDING VORTEX



BLUNT SAFETY BLADE

10X STRONGER

THAN TRADITIONAL BLADES



ULTRA HIGH-SPEED MOTOR

3.8 PEAK HP

BLENDS THE TOUGHEST INGREDIENTS

•	MOTOR	3.8 peak horsepower, 15 AMP/12OV or 7.5 AMP/24OV available
(3)	INTERFACE	Illuminated LED touchscreen display with operator controlled variable speed slider
	SOUND ENCLOSURE	Fully enclosed, easy-to-clean blending station. Advanced sound enclosure helps blender operate at nearly the sound level of normal conversation
42	PROGRAM CYCLES	42 preprogrammed cycles, customizable blend cycles with the Blend Wizard™ online tool
#	USAGE	Recommended daily blends: 200
<b>(3)</b>	DIMENSIONS	H: 17.3" (43.9 cm) D: 9.0" (22.9 cm) W: 8.6" (21.8 cm)
(b)	WEIGHT	15.8 lbs (7.2 kg)
<del>(+)</del>	ADDITIONAL FEATURES	Power Save Mode - powers down after 15min, 1hr, 6hrs, 12hrs of idle time Safety Interlock Setting - interrupts operation when sound enclosure is open

NSF CE ROHS



**CERTIFICATIONS** 

